

# RP RANGE


Salamander Pumps 

A range of premium pumps designed for smooth running with high levels of flow to boost pressure to appliances throughout the home. They can boost supplies to washbasins, baths, and showers. The centrifugal impeller gives them the quiet running with sustained pressure and flow relative to other shower pump types.




## Features

- More Pressure and Flow
- Impressively quiet
- Easy to install
- Continuously Rated
- Compact Salamander exclusive seal
- AV Couplers included
- 15/22mm push fit flexible hoses with integral isolating valves on inlets
- Pre-wired with power cable
- 3 years warranty
- Long life
- Centrifugal technology



- **UK Specification:** Supplied with 15/22mm pushfit x  $\frac{3}{4}$  anti-vibration flexible hoses.
- **ROI Specification:** Supplied with 21mm pushfit x  $\frac{3}{4}$  anti-vibration flexible hoses.



We're here to help before, during and after installation. Get in touch for guidance by calling our Pumpwise team or email [tech@salamanderpumps.co.uk](mailto:tech@salamanderpumps.co.uk)

**Pumpwise**  
0191 516 2002

# RP Technical Specification

Pump Model		RP50 PT	RP75 PT	RP100 PT
General	Guarantee	3 years		
	WRAS Approval	1810090		
Features	Pump Type	Centrifugal		
	Mechanical seal	Nitrile/ PTFE/ Ceramic		
	Inlet Isolator(s)	✓	✓	✓
	Flexible Hoses	4	4	4
Performance	Pressure @ 16lpm (8lpm for singles)	1.2 Bar	1.9 Bar	2.65 Bar
	Pressure @ 8lpm (4lpm for singles)	1.35 Bar	2.1 Bar	2.85 Bar
	Pressure @ Closed Head	1.5 Bar	2.2 Bar	3.0 Bar
	Maximum Water Temperature	65°C		
Connections	Pump connections	¾" BSP		
Flexible hoses	Connections (UK Model) <i>Isolating valves on all hoses</i>	¾" Female x 15mm Push-Fit x 180mm Straight 220mm Angled long	¾" Female x 22mm Push-Fit x 280mm long.	
Motor	Type	A.C Induction Motor		
	Duty Rating	Continuously Rated		
Electrical	Power supply	230 V		
	Current (full load)	1.40 Amps	2.70 Amps	4.60 Amps
	Power consumption	325 Watts	630 Watts	1045 Watts
	Fuse rating	3 Amps	5 Amps	
	Power cable (pre-wired)	1.5 metres		
Physical	Enclosure Protection (IP Rating)	IPX3		
	Length	270mm	331mm	415mm
	Width	148mm		
	Height (Excluding Hoses)	161mm	161mm	170mm
	Weight (Excluding Hoses)	4.82kg	6.03kg	9.06kg

# Why Choose a Right Pump?

## **STRONG MANUFACTURING HISTORY**

Salamander have been manufacturing the right pump centrifugal range for 20 years with constant modifications and performance improvements so that it stands in today's market as the go to product for whole house/multi shower applications.

The RP100 is the leading, most trusted three stage centrifugal pump and is used by plumbers nationwide.

## **10MM SELF-HEALING SEAL**

Salamanders exclusive compact seal which has the ability to heal itself if a leak originates from that area. The seal will prevent this leak happening again so that the owner does not find themselves with a re-occurring problem.

## **MULTI OUTLET USE**

RP pumps are supplied with a bypass tube meaning these twin-ended pumps are uniquely equipped to handle single or multi outlet use i.e. the hot or cold taps being used individually or both at the same time. This bypass uses similar crossover technology to the one used in the CT Bathroom range.

## **QUIET PUMP GUARANTEE**

Salamanders Right Pump range is guaranteed to offer a quieter operating noise level than those of its type in the centrifugal market. This sound level difference can be as great as 6.5 Db.

## **SPIDERS WEB OUTLET DESIGN**

The innovative design solution resembles a spider's web that has a greater tensile strength and elasticity. Its microstructure of radials and spirals has been applied by Salamander for the first time in shower pump design to maximise rigidity.