

Salamander Pumps



Gravity Fed Pump Comparison



CT Xtra				CT Bathroom				CT Force									Ora		Right Pumps									TapBoost	
CT55	CT85	CT50	CT75	CT60B	CT80B	CT60BU	CT80BU	CTF20PS	CTF30PS	CTF20SU	CTF30SU	CTF15PT	CTF20PT	CTF30PT	CTF15TU	CTF20TU	CTF30TU	ORA15	ORA2.0	RP55SU	RP80SU	RP120SU	RP50PT	RP75PT	RP100PT	RP50TU	RP75TU		RP100TU
Regenerative pumps for gravity-fed installation																	Centrifugal pumps for gravity-fed installation												

Twin or Single																																		
Single - boosts hot or cold water	•	•								•	•	•	•																					•
Twin - boosts hot and cold water			•	•	•	•	•						•	•	•	•	•	•	•							•	•	•	•	•	•			
Pump pressure rating																																		
Maximum pressure (Bar)	15	2.2	15	2.0	18	2.6	18	2.6	20	30	20	30	15	20	30	15	20	30	15	2.0	15	24	36	15	2.2	30	15	2.2	30			0.5		
System type																																		
Positive head system	•	•	•	•	•	•			•	•			•	•	•				•	•				•	•	•						•		
Negative head system							•	•			•	•				•	•	•			•	•	•				•	•	•					
Number of outlets																																		
Shower (1 outlet)	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
Individual tap/outlet (1 outlet)	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	
Bathroom (up to 2 outlets)					•	•	•	•	•	•	•	•	•	•	•	•	•	•			•	•	•	•	•	•	•	•	•	•	•	•		
Bathroom (up to 4 outlets)						•	•		•	•	•	•	•	•	•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•		
Whole house (up to 6 outlets)																•	•					•	•		•	•	•	•	•	•	•	•		
Whole house (up to 8 outlets)																						•	•		•	•		•	•	•	•	•		
Suitable outlets																																		
Thermostatic mixer shower (hot and cold)			•	•	•	•	•	•					•	•	•	•	•	•	•	•				•	•	•	•	•	•	•	•	•		
Thermostatic mixer shower (hot or cold)	•	•					•	•			•	•				•	•	•			•	•	•				•	•	•	•	•	•		
Mixer tap (hot and cold)					•	•	•	•					•	•	•	•	•	•							•	•	•	•	•	•	•	•		
Mixer tap (hot or cold)							•	•			•	•				•	•	•			•	•	•				•	•	•	•	•	•		
Pillar taps (hot and cold)					•	•	•	•					•	•	•	•	•	•							•	•	•	•	•	•	•	•	•	
Individual pillar tap (hot or cold)	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	•			•	•	•	•	•	•	•	•	•	•	•	•	•	
Drench shower head						•	•					•	•			•	•	•			•	•	•	•	•	•	•	•	•	•	•	•		
Body jets (4 max)							•				•						•						•									•		
Pump noise																																		
dBa rating*	From 44.5dBa				From 53.5dBa				From 42dBa									N/A		From 45.5dBa									34.2dBa					
Warranty																																		
Duration	3 years				3 years				5 years									1 year		3 years									2 years					

